

## TEREX Halco 2" DTH Hammer Range

### Dominator 100

The Dominator 100 is designed for small diameter drilling operations and its superior drilling performance makes it at least 50% faster than its nearest competitor

- Suitable for operation at air pressures of 7-17 Bar (100-250psi)
- Drilling diameters from 55mm - 66mm
- The valveless design of the Dominator 100 provides high performance at both low and high pressures
- Strong robust design withstands heavy duty applications
- A non return valve is fitted into the Dominator 100 improving its performance where ground water is present

HAMMER TYPE	DOMINATOR 100
PART NUMBER	600251
SHANK	HALCO DOMINATOR 100
TOP THREAD	40mm DIN 405 6TPI BOX
WEIGHT	7Kg
OUTSIDE DIAMETER	47mm (1.850")
MAKE UP LENGTH	772MM (30.394")
RECOMMENDED MAXIMUM THRUST	120kG (264 lbs)

### MACH 20

- Suitable for operation at air pressures of 7-17 Bar (100-250psi)
- The valved design of the Mach 20 provides high performance at low pressures
- Strong robust design withstands heavy duty applications
- Drilling diameters from 70mm - 80mm
- All steel valve provides reliable operation and avoids the possibility of heat distortion
- Three levels of air volume with a variety of chokes available

HAMMER TYPE	MACH 20	MACH 20
PART NUMBER	600169	600209
SHANK	HALCO MACH 20	HALCO MACH 20
TOP THREAD	50mm DIN 405 6TPI BOX	40mm DIN 405 6TPI BOX
WEIGHT	13Kg	13Kg
OUTSIDE DIAMETER	62mm (2.441")	62mm (2.441")
MAKE UP LENGTH	840mm (33.070")	840mm (33.070")
RECOMMENDED MAXIMUM THRUST	150Kg (330 lbs)	150Kg (330 lbs)