

Return to [www.bitbrokers.com](http://www.bitbrokers.com)

## TEREX Halco 3" DTH Hammer Range

### MACH 303

Mach 303 General purpose hammer for small hole drilling. In applications such as seismic and geological survey, micro-piling, floor, wall and roof bolting or for blast holes where environmental considerations limit hole size and blasting procedure. Suitable for drilling at a wide range of air pressures in both soft and hard rock conditions.

HAMMER TYPE	MACH 303
PART NUMBER	600080
SHANK	HALCO MACH 303
TOP THREAD	2 3/8 API REG PIN
WEIGHT	20Kg
OUTSIDE DIAMETER	77mm (3.031")
MAKE UP LENGTH	882mm (32.362")
RECOMMENDED MAXIMUM THRUST	150Kg (330 lbs)
RECOMMENDED MAXIMUM THRUST	300Kg (660 lbs)

### DART 350

Dart 350 hammer gives up to 25% increase in performance compared to conventional 2" hammers. Particularly suitable for low pressure operation although capable of working between 7-24 Bar (100-350psi). Drilling diameters 90mm - 104mm (3.1/2" - 4.3/32").

HAMMER TYPE	DART 350	DART 350 (NO NRV)
PART NUMBER	600198	600303
SHANK	IR 3.5	IR 3.5
TOP THREAD	2 3/8 API REG PIN	2 3/8 API REG PIN
WEIGHT	23Kg	23Kg
OUTSIDE DIAMETER	81mm (3.189")	81mm (3.189")
MAKE UP LENGTH	832mm (32.756")	832mm (32.756")
RECOMMENDED MAXIMUM THRUST	150Kg (330 lbs)	150Kg (330 lbs)
RECOMMENDED MAXIMUM THRUST	300 Kg (660 lbs)	300 Kg (660 lbs)

### DOMINATOR 350

Dominator 350 hammer is a high performance hammer for medium to hard rock conditions. Operates at an optimum air pressure between 14-24 Bar (200 - 350psi).

HAMMER TYPE	DOMINATOR 350
PART NUMBER	600199
SHANK	IR 3.5
TOP THREAD	2 3/8 API REG PIN
WEIGHT	23Kg
OUTSIDE DIAMETER	81mm (3.189")
MAKE UP LENGTH	832mm (32.756")
RECOMMENDED MAXIMUM THRUST	150Kg (330 lbs)
RECOMMENDED MAXIMUM THRUST	300 Kg (660 lbs)