

TEREX Halco 4" DTH Hammer Range

NT4

The NT4 has been specifically designed for high production drilling in blast hole applications. The hammer is simple, robust and has few parts, making it user friendly and reliable. The NT4 utilizes Halco's all new 12 spline shank which has simplistic robust geometry combined with increased drive contact area.

HAMMER TYPE	NT4
PART NUMBER	600354
SHANK	HALCO NT4
TOP THREAD	2 3/8 API REG PIN
WEIGHT	38.5Kg
OUTSIDE DIAMETER	100.5 mm (4.956")
MAKE UP LENGTH	914mm (35.984")
RECOMMENDED MAXIMUM THRUST	250Kg (550 lbs)
RECOMMENDED MAXIMUM THRUST	500Kg (1100 lbs)

MACH 44

The Mach 44 is a general purpose hammer used at pressures up to and including 350 PSI (24 Bar). It is suitable for all rock conditions at a wide range of air pressures. The Mach 44 has a proven track record of performance and reliability.

HAMMER TYPE	DART 350
PART NUMBER	600070
SHANK	HALCO MACH 44
TOP THREAD	2 3/8 API REG PIN
WEIGHT	35.3Kg
OUTSIDE DIAMETER	95mm (3.750")
MAKE UP LENGTH	1000mm (39.375")
RECOMMENDED MAXIMUM THRUST	250Kg (550 lbs)
RECOMMENDED MAXIMUM THRUST	500Kg (1100 lbs)

SUPER DOMINATOR 400

The Super Dominator 400 is designed for maximum performance at higher pressures, up to and including 350 PSI (24 Bar). The Super Dominator is a heavy duty hammer with thicker 98mm diameter outer components to provide an extended service life in abrasive conditions and is also suitable for well drilling.

HAMMER TYPE	SUPER DOMINATOR 400		
PART NUMBER	600224	600226	600258
SHANK	HALCO MACH 44	SANDVIK MISSION A34-15/SD4	INGERSOLL RAND DHD340A
TOP THREAD	2 3/8 API REG PIN	2 3/8 API REG PIN	2 3/8 API REG PIN
WEIGHT	38Kg	38Kg	38Kg
OUTSIDE DIAMETER	98mm (3.875")	98mm (3.875")	98mm (3.875")
MAKE UP LENGTH	1042mm (41")	1042mm (41")	1042mm (41")
RECOMMENDED MAXIMUM THRUST	250Kg (550 lbs)	250Kg (550 lbs)	250Kg (550 lbs)
RECOMMENDED MAXIMUM THRUST	500Kg (1100 lbs)	500Kg (1100 lbs)	500Kg (1100 lbs)