

TEREX Halco 6" DTH Hammer Range

NT6

The NT6 has been specifically designed for high production drilling in blast hole applications. Halco have increased the hammer's air pressure making easy going of the hardest rock structures. The NT6 hammers are available in a heavy duty version for increased life in abrasive conditions, and an extra version specifically for deep hole drilling.

HAMMER TYPE	NT5	NT5E	NT5HD	NT5HD
PART NUMBER	600333	600334	600336	600364
SHANK	INGERSOLL RAND QL60	INGERSOLL RAND QL60	INGERSOLL RAND QL60	INGERSOLL RAND QL60
TOP THREAD	3 1/2 API REG PIN	3 1/2 API REG PIN	3 1/2 API REG PIN	3 1/2 API REG PIN
WEIGHT	107Kg	107Kg	110Kg	110Kg
OUTSIDE DIAMETER	140mm (5.512")	140mm (5.512")	146mm (5.748")	146mm (5.748")
MAKE UP LENGTH	1063mm (41.850")	1063mm (41.850")	1063mm (41.850")	1063mm (41.850")
RECOMMENDED MAXIMUM THRUST	500Kg (1100 lbs)	500Kg (1100 lbs)	500Kg (1100 lbs)	500Kg (1100 lbs)
RECOMMENDED MAXIMUM THRUST	1500Kg (3300 lbs)	1500Kg (3300 lbs)	1500Kg (3300 lbs)	1500Kg (3300 lbs)

SUPER DOMINATOR 600

The Super Dominator 600 is one of the fastest 6" hammers specifically designed for high production drilling in blast hole applications. The Super Dominator 600, is a reduced weight hammer with water well drilling capabilities.

HAMMER TYPE	SUPER DOMINATOR 600
PART NUMBER	600272
SHANK	INGERSOLL RAND DHD360
TOP THREAD	3 1/2 API REG PIN
WEIGHT	100Kg
OUTSIDE DIAMETER	140mm (5.511")
MAKE UP LENGTH	1139mm (44.842")
RECOMMENDED MAXIMUM THRUST	500Kg (1100 lbs)
RECOMMENDED MAXIMUM THRUST	1500Kg (3300 lbs)

SUPER DOMINATOR 650

The Super Dominator 650 combines the raw power of the Super Dominator 600 with extended hammer life in abrasive conditions due to its heavy duty outside diameter and reversible cylinder. With a recommended minimum bit size of 6 3/4".

HAMMER TYPE	SUPER	DOMINATOR 650
PART NUMBER	600213	600233
SHANK	INGERSOLL RAND DHD350	SANDVIK MISSION A53-15/SD6
TOP THREAD	3 1/2 API REG PIN	3 1/2 API REG PIN
WEIGHT	104Kg	104Kg
OUTSIDE DIAMETER	146mm (5.748")	146mm (5.748")
MAKE UP LENGTH	1139mm (44.842")	1139mm (44.842")
RECOMMENDED MAXIMUM THRUST	500Kg (1100 lbs)	500Kg (1100 lbs)
RECOMMENDED MAXIMUM THRUST	1500Kg (3300 lbs)	1500Kg (3300 lbs)

MACH 60

The Mach 60 is a versatile and reliable hammer. Economical to operate due to its relatively low air consumption. A reversible cylinder further reduces running costs by extending hammer life.

HAMMER TYPE	MACH 60
PART NUMBER	600035
SHANK	HALCO MACH 60
TOP THREAD	3 1/2 API REG PIN
WEIGHT	89Kg
OUTSIDE DIAMETER	138mm (5.433")
MAKE UP LENGTH	1095mm (43.110")
RECOMMENDED MAXIMUM THRUST	500Kg (1100 lbs)
RECOMMENDED MAXIMUM THRUST	1500Kg (3300 lbs)

DOMINATOR 600

The Dominator 600 is a class leader in performance and is suitable for drilling at a wide range of air pressures, excelling at higher working pressures. With water well drilling capabilities and a recommended minimum bit size of 6".

HAMMER TYPE	DOMINATOR 600		
PART NUMBER	600094	600151	600152
SHANK	INGERSOLL RAND DHD360	HALCO MACH 60	SANDVIK MISSION A53-25
TOP THREAD	3 1/2 API REG PIN	2 3/8 API REG PIN	3 1/2 API REG PIN
WEIGHT	89Kg	89Kg	89Kg
OUTSIDE DIAMETER	139mm (5.472")	139mm (5.472")	139mm (5.472")
MAKE UP LENGTH	1208mm (47.559")	1208mm (47.559")	1208mm (47.559")
RECOMMENDED MAXIMUM THRUST	500Kg (1100 lbs)	500Kg (1100 lbs)	500Kg (1100 lbs)
RECOMMENDED MAXIMUM THRUST	1500Kg (3300 lbs)	1500Kg (3300 lbs)	1500Kg (3300 lbs)